



## DC1000B M.2 NVMe SSD

### Boot Drive for Enterprise Servers

---

Kingston's Data Centre DC1000B is a high-performance M.2 (2280) NVMe PCIe SSD using the latest Gen 3.0 x 4 PCIe interface with 64-layer 3D TLC NAND. DC1000B offers data centres a cost-effective boot drive solution with the reassurance they are purchasing an SSD designed for server use. The DC1000B is ideally suited for use in high-volume rack-mount servers as an internal boot drive(s) as well as for use in purpose-built systems where a high-performance M.2 SSD is needed that includes on-board power loss protection (PLP).

---

- M.2 (2280) NVMe PCIe SSD Gen 3.0 x 4, performance
- NVMe for server boot workloads
- Application-optimised capacities keep costs low
- On-board (PLP) Power Loss Protection
- Self-Encrypting Drive (SED) with AES-XTS 256bit

#### Enterprise Data Centre NVMe Boot SSD

M.2 NVMe SSDs are evolving within the data centre providing efficiencies in booting servers to preserve valuable front-loading drive bays for data storage. Whitebox and Tier 1 Server OEMs are beginning to equip server motherboards with one or sometimes two M.2 sockets for boot purposes. While the M.2 form-factor was originally designed as a client SSD form-factor, its small physical size and high performance make it attractive for server use. Not all SSD are created equal and using a client

SSD in a server application may result in poor inconsistent performance.

### Applications

Boot drives are used primarily for booting an OS, but in many use cases today the boot drive has a secondary purpose; logging application data and/or configured as a high-speed local cache drive. Therefore, the DC1000B was designed with added endurance (0.5 DWPD for 5yrs) to handle the OS workload as well as the extra write workload of caching and data logging. In addition to being designed for long term reliability the DC1000B is designed to deliver enterprise level performance consistency and low latency features typically not found on client SSDs. Available in 240GB and 480GB capacities<sup>1</sup>.

## Key Features

- M.2 (2280) NVMe Performance**  
 Incredible speeds of up to 2.6GB/s and 200K IOPS.
- Optimised Server Boot Drive**  
 Enhanced for boot workloads as well as caching and logging applications.
- On-board (PLP) Power Loss Protection**  
 Reduce the possibility of data loss and/or corruption on ungraceful power-off.
- Maximise Drive Bays**  
 Move boot drives internally frees up front loading drive bays for additional data storage.

## Specifications

Form Factor	M.2, 22mm x 80mm (2280)
Interface	PCIe NVMe Gen3 x4
Capacities <sup>1</sup>	240GB, 480GB
NAND	3D TLC
Self-Encrypting Drive (SED)	AES 256-bit Encryption
Sequential Read/Write	240GB – 2,200MBs/290MBs 480GB – 3,200MBs/565MBs

Steady-State 4k Read/Write <sup>2</sup>	240GB – 111.000/12.000 IOPS 480GB – 205.000/20.000 IOPS
Latency Read (Avg)	161µs
Latency Write (Avg)	75µs
Power Loss Protection (Power Caps)	Yes
SMART Health Monitoring and Telemetry	SMART, Telemetry and other Enterprise Class Diagnostic capabilities
Endurance	240GB — 248TBW (0.5 DWPD/5yrs) <sup>3</sup> 480GB — 475TBW (0.5 DWPD/5yrs) <sup>3</sup>
Power Consumption	240GB: Idle: 1.82W Average Read: 1.71W Average Write: 3.16W Max Read: 1.81W Max Write: 3.56W 480GB: Idle: 1.90W Average Read: 1.74W Average Write: 4.88W Max Read: 1.81W Max Write: 5.47W
Storage temperature	-40°C ~ 85°C
Operating temperature	0°C ~ 70°C
Dimensions	80mm x 22mm x 3.8mm
Weight	240GB – 8g 480GB – 9g
Vibration operating	2.17G Peak (7–800Hz)
Vibration non-operating	20G Peak (10–2000Hz)

---

MTBF	2 million hours
Warranty/support <sup>4</sup>	Limited 5-year warranty with free technical support

## Part Numbers

### SEDC1000BM8

SEDC1000BM8/240G
SEDC1000BM8/480G

## Product Image



1. Some of the listed capacity on a Flash storage device is used for formatting and other functions and thus is not available for data storage. As such, the actual available capacity for data storage is less than what is listed on the product. For more information go to [Kingston's Flash Memory Guide](#).
2. Measurement taken once the workload has reached steady state but including all background activities required for normal operation and data reliability.
3. [Total Bytes Written](#) (TBW) and [Drives Writes Per Day](#) (DWPD) derived from the JEDEC Enterprise Workload (JESD219A).
4. Limited warranty based on 5 years or "SSD Life Remaining" which can be found using the Kingston SSD Manager ([Kingston.com/SSDManager](http://Kingston.com/SSDManager)). A new, unused product will show a wear indicator value of one hundred (100), whereas a product that has reached its endurance limit of program erase cycles will show a wear indicator value of one (1). See [Kingston.com/wa](http://Kingston.com/wa) for details.



THIS DOCUMENT SUBJECT TO CHANGE WITHOUT NOTICE.

©2024 Kingston Technology Europe Co LLP and Kingston Digital Europe Co LLP, Kingston Court, Brooklands Close, Sunbury-on-Thames, Middlesex, TW16 7EP, England. Tel: +44 (0) 1932 738888 Fax: +44 (0) 1932 785469 All rights reserved. All trademarks and registered trademarks are the property of their respective owners. MKD-04082024